



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 46,7 |
| B | 20,6 |
| C | 4 |
| D | 33,8 |
| E | 41,4 |
| F | 39,7 |
| G | 50,8 |
| H | 3,7 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 8 | DOSENGEHÄUSE / SHELL |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

| Material Specification: | |
|-------------------------|-----------------|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Nickel plated |
| Insulator Material: | CR-Elastomere |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m
 drawing for CUSTOMER

| | | |
|---|-------------|---------------------------------------|
| ITT <i>Engineered for life</i> <small>ITT CANNON GmbH D - 71384 Weinstadt/Germany</small> | description | CA02COM-E28-15S-B-01 |
| | | Box mounting receptacle |
| | | Metric Crimp / Socket / Layout: 28-15 |