


PCB-14S05



Bohrung Achse	Lage / position	
	X-Achse X-axe ±0,05	Y-Achse Y-axe ±0,05
A	0,00	3,70
B	3,50	1,15
C	2,15	-2,95
D	-2,15	-2,95
E	-3,50	1,15

5 PC-Kontaktbohrungen Ø1±0,1

Ansicht ist auf der Steckseite Stift-Stecker gezeichnet.

Für Steckseite Buchsen-Stecker ist das Bohrbild spiegelbildlich zur Hauptachse (↕)

Für Winkelverdrehung sind die Koordinaten entsprechend umzurechnen

5 PC-contact holes Ø1±0,1

View on mating face of pin-connector

For mating face of socket-connector the hole pattern is symmetrically to the main axis (↕)

For angular rotation the coordinates must be changed accordingly

Winkelverdrehung: X = 110°
angular rotations:



Ø1 H9	shell type
CA 02	CA 28
34	45

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change
Drawings illustrate normal insulator positioning

Material Specification:

Shell Material: Aluminium alloy

Shell Plating: Nickel plated

Insulator Material: CR-Elastomere

Contact Material: Copper alloy

Contact Plating: Hard silver

all dimensions are in mm
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
CUSTOMER



Engineered for life
ITT CANNON GmbH
D - 71384 Weinstadt/Germany

description CA02COM-L14S-5S-B
Box mounting receptacle

PCB Ø 0,76 / Socket / Layout: 14S-5

© All rights reserved. Reproduction or issue to third in any form
whenever is only permitted with written authorization of ITT Cannon



page 2/2
revision 1029 28. Mar 24