



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 46,6 |
| B | M32X1,5 |
| C | 40,5 |
| D | 74 |
| E | 12 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|----------------------------------------|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5 | KONTAKTSTIFT / CONTACT PIN |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 10 | DICHTRING FRONT / FRONT SEALING RING |
| 11 | O-RING ENDGEHÄUSE / O-RING ENDBELL |
| 15 | METRISCHES ENDGEHÄUSE / METRIC ENDBELL |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

| Material Specification: | |
|-------------------------|-----------------|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Nickel plated |
| Insulator Material: | CR-Elastomere |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m
 drawing for CUSTOMER



description CA06COM-ME24-28P-B
 Plug, straight
 Endbell for metric cable gland termination
 Solder Cup / Pin / Layout: 24-28

© All rights reserved. Reproduction or issue to third in any form whatever is only permitted with written authorization of ITT Cannon
 page 1/1
 revision 1029 28. Mar 24