


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 40,5 |
| B | 1 3/18UNEF-2A |
| C | 82 |
| D | 29,5 |
| E | 9 |
| F | PG21 |


| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 10 | DICHTRING FRONT / FRONT SEALING RING |
| 11 | O-RING ENDGEHÄUSE / O-RING ENDBELL |
| 15 | PG-ENDGEHÄUSE / PG-ENDBELL |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning and installed contacts

| Material Specification: | |
|-------------------------|-----------------|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Nickel plated |
| Insulator Material: | CR-Elastomere |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m
 drawing for CUSTOMER

| | | |
|--|-------------|--|
|  ITT <i>Engineered for life</i> <small>ITT CANNON GmbH D - 71384 Weinstadt/Germany</small> | description | CA08COM-PG22-23S-F0 |
| | | Plug 90° |
| | | Endbell for PG cable gland termination |
| | | Solder Cup / Socket / Layout: 22-23 |
| | | Delivery without contacts |

© All rights reserved. Reproduction or issue to third in any form
 whatever is only permitted with written authorization of ITT Cannon

| | |
|------|-----------------|
| page | revision |
| 1/1 | 1024 28. Mar 24 |