


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 34.1 |
| B | 1 1/8-18UNEF-2B |
| C | 1-20UNEF-2A |
| D | 37.7 |


| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|-------------------------------------|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5 | KONTAKTSTIFT/ CONTACT PIN |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

| Material Specification: | |
|-------------------------|--|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Olive drab chromate coating over cadmium plating |
| Insulator Material: | Neoprene |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m
 drawing for
 CUSTOMER


ITT
Engineered for life
ITT CANNON GmbH
 D - 71384 Weinstadt/Germany

description **CA3106E18-10P-F42**
Plug, straight
 without Endbell and grommet
 Solder Cup / Pin / Layout: 18-10