


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| D1 | 19.8 |
| D2 | 8.9 |
| D3 | 6.7 |
| D4 | 13.3 |
| D5 | 16 |
| E | 0.23 |
| K | 3.89 |
| L1 | 48 |
| L2 | 21.4 |
| L3 | 15 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|--|
| 1 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 2 | ISOLIERKÖRPER MITTE / WAYER |
| 4 | DICHTKÖRPER / GROMMET |
| 7 | KONTAKT BUCHSE / CONTACT SOCKET |
| 8 | GEHÄUSE / RECEPTACLE |
| 12 | ÜBERWURFMUTTER / COUPLING NUT |
| 13 | ÜBERWURFMUTTER F. ENDGEH. / COUPLING NUT |
| 14 | WELLFEDER / WASHER |
| 17 | ADAPTER / ADAPTER |
| 18 | KLEMM-MUTTER / CLAMP NUT |
| 21 | DRAHT / FIXING WIRE |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

| Material Specification: | |
|-------------------------|--|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Zinc cobalt, black |
| Insulator Material: | Polychloroprene |
| Contact Material: | Copper alloy |
| Contact Plating: | #12/16:gold plated, #20:contact area gold plated |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
 CUSTOMER



description KPSE6E8-3AS-DZ-A232
 Straight plug
 Endbell for shielding braids and shrink boots
 Crimp Contacts / Socket / Layout: 83A

© All rights reserved. Reproduction or issue to third in any form
 whoever is only permitted with written authorization of ITT Cannon

page 1/1
 revision 4674 13. Sep 24